KME / ER COOLER LINE UP



(Outdoor Unit Back Type)

POWER SOURCE: 12VDC or 24VDC


MAXIMUM INPUT: 720 W (Input Current: 60A(12VDC) / 30A(24VDC))

MAXIMUM COOLING CAPACITY: 2,200 W (7,510 Btu/h) SETTING TEMPERATURE: 18 degrees to 28 degrees

REFRIGERANT: HFC-134a

DIMENSION & WEIGHT:

(Please see the right side.)





Weight: 6.0kgs



Weight: 18.5kg

IK12T/K24T

(Outdoor Unit Top Type)

POWER SOURCE: 12VDC or 24VDC

MAXIMUM INPUT: 720 W (Input Current: 60A(12VDC) / 30A(24VDC))

MAXIMUM COOLING CAPACITY: 2,200 W (7,510 Btu/h) SETTING TEMPERATURE: 18 degrees to 28 degrees

REFRIGERANT: HFC-134a

DIMENSION & WEIGHT:

(Please see the right side.)



©690mm **6**445mm **6**265mm

IK12U/K24U

(Outdoor Unit Multi Type)

POWER SOURCE: 12VDC or 24VDC

MAXIMUM INPUT: 720 W (Input Current: 60A(12VDC) / 30A(24VDC))

MAXIMUM COOLING CAPACITY: 2,200 W (7,510 Btu/h) SETTING TEMPERATURE: 18 degrees to 28 degrees

REFRIGERANT: HFC-134a

DIMENSION & WEIGHT:

(Please see the right side.)



©510mm **⊜**320mm

6325mm

■Indoor Unit

2 Types Indoor Unit & 2 Colors Cover

Under Installation



Side Installation



WHITE



GRAY



2020 Year New Release



- 200mm (D)

Smart Choice for your Motor Home Life!

