

INVERTER DRIVER



Model No. : DPC-29-0140-A

Power Source : AC85~264V/1-phase/(50/60Hz)
Output Power : 500W(MAX)
Speed Control : PWM
Speed Range : 20~80rps
Dimensions : 160×146×60mm
180×146×65mm(with Heatsink)

Operation Temperature Range : -10~50°C
Operation Humidity Range : 30~80%RH
Storage Temperature Range : -20~70°C
Storage Humidity Range : 10~95%RH



Model No. : DPC-29-0070-C

Power Source : AC180~264V/1-phase/(50/60Hz)
Output Power : 3200W(MAX)
Speed Control : PWM/0~10V/4~20mA
Speed Range : 15~120rps
Dimensions : 160×145×70mm
177×160×112mm(with Heatsink)

Operation Temperature Range : -10~50°C
Operation Humidity Range : 30~80%RH
Storage Temperature Range : -20~70°C
Storage Humidity Range : 10~95%RH



Model No. : DPP-109-07-A20A

Power Source : AC180~264V/1-phase/(50/60Hz)
Output Power : 6200W(MAX)
Speed Control : RS485
Speed Range : 15~120rps
Dimensions : 242×182×75mm
242×182×120mm(with Heatsink)

Operation Temperature Range : -10~50°C
Operation Humidity Range : 30~80%RH
Storage Temperature Range : -20~70°C
Storage Humidity Range : 10~95%RH



Model No. : DPP-232-02A-21A

Power Source : AC180~264V/3-phase/(50/60Hz)
Output Power : 8000W(MAX)
Speed Control : RS485
Speed Range : 15~120rps
Dimensions : 170×160×105mm

Operation Temperature Range : -10~50°C
Operation Humidity Range : 30~80%RH
Storage Temperature Range : -20~70°C
Storage Humidity Range : 10~95%RH